

DUAL LIGHT MODULE WITH MOUNTING BRACKET



The perimeter alarm light system can be installed onto most of the Nemtek electric fencing brackets and posts. The lights are installed at 6m to 9m intervals along the electric fence line to illuminate the area. When the electric fence energizer alarms, the perimeter alarm lights will illuminate the specific zone that has been triggered. This could help detect, and thus deter, the intruder from attacking the fence line. The lights are LED, consuming low energy and will be illuminated immediately. They face downward, thus minimising light pollution.

Features:

- System is powered by a 2.0Amp Nemtek Power Pack with a 7Ah battery for back up during power failures
- A single power pack can provide power to 20 sets of lights (40 in total)
- Lights are installed at 6m to 9m intervals along the fence line with 200m coverage on a power pack
- Lights are downward facing
- Lights are LED so no warm-up time is required
- Lights can be triggered in three ways:
 - Energizer alarm trigger
 - Remote on and off
 - Day/night switch
- Wet/dry contacts are configurable on the power-supply trigger module
- Low-voltage cabling is run along the fence line to provide power to the lights

Specifications:

IP rating	IP67
Input voltage	20 – 30VDC
Current consumption	40mA
Operating temperature	-20° – 55°C
Minimum luminous intensity	99000mcd
Emission colour	Ultra bright white
Illumination angle	80°
Mounting	2 x 5mm holes

DUAL LIGHT MODULE WITH MOUNTING BRACKET



Stock Code	Description
SR-FL/DUAL	Dual light module with mounting bracket